

Communication Convertor

IFD

6500 USB to RS-485 Converter

- ▲ Max.baud rate:115.2kbps
- ▲ No external power supply required
- ▲ Auto-detects the direction of data flow
- ▲ Portable USB device



IFD

6503 USB to CAN Converter

- ▲ Able to extract CAN message (Including standard frame & extended frame)
- ▲ Able to filter by set conditions
- ▲ Able to send CAN messages (single messages by manual mode,max.8messages by auto mode)
- ▲ Max.baud rate :1Mbps
- ▲ Portable USB device

IFD

6530 USB to RS-485 Converter

- ▲ Offers 9V power supply for parameter storage and page editing through KPC-CC01(VFD-C2000 keypad)
- ▲ Max.baud rate:115.2kbps
- ▲ No external power supply required
- ▲ Auto-detects the direction of data flow
- ▲ Portable USB device



IFD

8500

RS-232 to RS-422/485 Isolated Converter

IFD

8510

RS-232 to RS-422/485 Isolated Repeater

- ▲ Extends the communication distance of RS-422/485 to 1.2km and connectable to 32 RS-485 devices

IFD

8520

RS-232 to RS-422/485 Addressable Isolated Converter

- ▲ Able to connect the equipment with RS-232 interface to RS-422/485 by setting up correct Modbus address

Communication Convertor

IFD 9502

DeviceNet to Modbus Converter

- ▲ Complies with Devicenet format
- ▲ Connectable to all Delta's industrial automation products
- ▲ Isolation in all RS-485 channels(including power supply)
- ▲ Passed full compatibility test



IFD 9503

CANopen to Modbus Converter

- ▲ Complies with CANopen format
- ▲ Connectable to all Delta's industrial automation products
- ▲ Isolation in all RS-485 channels(including power supply)
- ▲ Passed full compatibility test



IFD 9506

Modbus TCP to Modbus Converter

- ▲ Isolation in all RS-485 channels(including power supply)
- ▲ Supports Modbus TCP Protocol
- ▲ Smart Monitoring
- ▲ Supports webpage setup & on-line monitoring
- ▲ Virtual COM serial port available
- ▲ E-mail alarm



IFD 9507

EtherNet/IP to Modbus Converter

- ▲ Isolation in all RS-485 channels(including power supply)
- ▲ Supports EtherNet/IP Protocol
- ▲ Smart Monitoring
- ▲ Supports webpage setup & on-line monitoring
- ▲ Virtual COM serial port available
- ▲ E-mail alarm

